



## 3 mm Round. Light Transporters, arrangeable in rows

### KSMJ01 / KSMD04 **Series**



# Series KSMJ01-XX 5.08 3.5 1.81 2.5 4.5 1 ł 2.5 5.08 5.08 L 5.08 Dimensions in mm (typical)

RECOMMENDED LEDS:				
Size	Color	Range intensity (mcd)		
1206	All	7,5÷140		
0805	All	2÷60		
0603	All	10÷60		



# Series KSMD04-XX 25.4 5.08 2.5 .54 5.08

	20.3	2	
	5.08	5.08	
† L 			
imension			5.08

RECOMMENDED LEDS:				
Size	Color	Range intensity		
		(mcd)		
0805	All	2÷60		
0603	All	10÷60		
0603	All	10÷60		

Туре	Length
KT-02	L = 2  mm
KT-04	L = 4 mm
KT-054	L = 5,4 mm
KT-06	L = 6 mm
KT-075	L = 7,5 mm
KT-085	L = 8,5 mm
KT-10	L = 10 mm
KT-13	L = 13 mm
KT-15	L = 15 mm
KT-17	L = 17 mm
KT-20	L = 20 mm
KT-25	L = 25 mm
KT-30	L = 30 mm
KT-37	L = 37,9 mm
KT-40	L = 40 mm
KT-45	L = 45 mm
KT-47	L = 47,5 mm
KT-50	L = 50 mm
Your length	L =


The code: KT-XX refers only to the transparent part. On the grounds of the desired length KT-XX can be supplied in rows of 3 or 8 places. We supply the complete device, that is black together with transparent part and the full code will be as follows: For example:


KSMD04 + KT30 = KSMD 04-30

#### **OPTIONS AVAILABLE**

- Other standard lengths from 1 to 50 mm
- Right angle
- Different shapes and lengths
- Different fixing systems on P.C.B.

### **One of many applications**





	2
	-

