

# SERIES KST 3504

Ø 3 mm LED

TYPE (4 LEDs)	EMITTED COLOUR	PEAK	LUMINOUS INTENSITY		FULL VIEWING ANGLE	FORWARD VOLTAGE (IF = 20 mA)		OPERATING TEMPERATURE	FORWARD CURRENT
			TYP.	IF		TYP.	MAX		
KST 3504 - R	RED	700	5	10	120	2,0	2,5	- 55 to + 100	25
KST 3504 - Y	YELLOW	590	12,5	10	120	2,1	2,5		30
KST 3504 - G	GREEN	565	12,5	10	120	2,2	2,5	25	
KST 3504 - S	SUPER RED	625	20	10	120	2,0	2,5	30	
KST 3504 - B	RED/GREEN	625/565	12,5	20	100	2,0	2,5	25	
KST 3504 - I	IPER RED	660	100	20	120	1,85	2,5	30	
KST 3504 - M	MULTICOLOURED		INDICATE COLOURS FROM LEFT TO RIGHT (SEE DRAWING)						
LOW CURRENT									
KST 3504 - RL	RED	625	2	2	120	1,8	2,5	- 55 to + 100	7,5
KST 3504 - YL	YELLOW	590	2	2	120	1,9	2,7		7,5
KST 3504 - GL	GREEN	565	2	2	120	1,9	2,5	7,5	
KST 3504 - IL	IPER RED	660	20	2	120	1,85	2,5	7,5	
QUALITY TESTED 100%	DIFFUSED	nm	mcd	mA	DEGREE°	V	V	°C	mA

