

SERIES KST 3801

Ø 3 mm LED

TYPE (1 LED)	EMITTED COLOUR	LUMINOUS INTENSITY		FULL VIEWING ANGLE	FORWARD VOLTAGE (IF = 20 mA)		OPERATING TEMPERATURE	FORWARD CURRENT	
		PEAK	TYP.		IF	TYP.			MAX
KST 3801 - R	RED	700	5	10	120	2,0	2,5	25	
KST 3801 - Y	YELLOW	590	12,5	10	120	2,1	2,5	30	
KST 3801 - G	GREEN	565	12,5	10	120	2,2	2,5	25	
KST 3801 - S	SUPER RED	625	20	10	120	2,0	2,5	30	
KST 3801 - B	RED/GREEN	625/565	12,5	20	120	2,0	2,5	25	
KST 3801 - I	IPEER RED	660	100	20	120	1,85	2,5	30	
LOW CURRENT									
KST 3801 - RL	RED	625	2	2	120	1,8	2,5	7,5	
KST 3801 - YL	YELLOW	590	2	2	120	1,9	2,7	7,5	
KST 3801 - GL	GREEN	565	2	2	120	1,9	2,5	7,5	
KST 3801 - IL	IPEER RED	660	20	2	120	1,85	2,5	7,5	
QUALITY TESTED 100%	DIFFUSED	nm	mcd	mA	DEGREE°	V	V	°C	mA

